Hot CCTV Surveillance Analog High Definition CCTV Bullet Video Cameras DR-A513100W3.6MM

Features and Functions:

- 1. Applied high-performance sensors, image more clear and delicate
- 2. Support IR-CUT double filter switching, monitor day and night, and color vivid
- 3. Analog high definition AHD-L@AHD video output
- 4. Support OSD menu, can adjust the pictures and functions freely
- 5. The transmission distance can up to 500meters
- 6. Need connect the back-end AHD DVR
- 7. Support the low intensity of illumination
- 8. Support the automatic electronic shutter function
- 9. Fit the IP66 waterproof, High Reliability
- 10. To implement million pixels in HD video transmission, with low cost, long distance, without delay, high efficiency, anti-interference and easy implement



Specifications

| Product | DR-A5131.0MP |
|-------------------------------|---|
| Sensor | 1/4" OV9712 CMOS |
| Signal System | AHD-L@AHD |
| Resolution | PAL: 1280*720 |
| Minimum illumination | Colors 0.1 Lux @(F1.2, AGC ON), 0 LUX with IR |
| | Black & white 0.01 Lux @ (F1.2, AGC ON), 0 LUX with IR |
| Shutter | 1/50(1/60)seconds to 1/10,000seconds |
| Day and night conversion mode | Support IR-CUT |
| Lens | HD special plate lens (3.6mm, 6mm) option |
| Interface of Lens | M12 |
| Video output | 1Vp-p composite output (75Ω/BNC) |
| Image settings | Saturation, brightness, contrast are set up through the OSD button menu |
| Working Temperature | − 10°C ~ 60°C, humidity less than 90% |
| and Humidity | (No condensation) |
| Power supply | DC12V±10% |
| IP Grade | IP66 |
| Power consumption | 6W MAX |
| Size | Φ63mm*166mm |
| Weight | 450g |

Application Scene:

Suitable for roads, warehouse, high-grade office buildings, underground parking garage and other places require for high-definition